

xsky

3 YEARS
WARRANTY



EN

Recessed spot lights for interior use, equipped with power LEDs.
Body and frame of extruded aluminum.
Frame with anodized aluminum finishing or electrostatically painted.
FRESNEL polycarbonate lens.
Constant current LED driver has to be ordered separately.

Range of applications

Decorative or general lighting.

RO

Spoturi încastrate pentru montaj în interior, echipate cu LED-uri de putere.
Corpul și rama din aluminiu extrudat.
Rama cu finisaj aluminiu anodizat sau vopsită în câmp electrostatic.
Lentilă FRESNEL din policarbonat.
Alimentatorul în curent constant se comandă separat.

Aplicații

Iluminatul decorativ sau general.

IT

Incassi fissi per interni equipaggiati con LED di potenza.
Corpo e telaio in alluminio estruso.
Telaio con finitura alluminio anodizzato o verniciato a polveri.
Lente FRESNEL in policarbonato.
Alimentatore a corrente costante da ordinare separatamente.

Campi di applicazione

Illuminazione decorativa o generale.

RECOMMENDED CC DRIVERS











LD350.3MINI ATD350.09

SK01

FINISHING AVAILABLE

MWH MBK AL-AN










Code	Finishing	LED type	Power	Output current /voltage pdriver	Driver	LED flux	System flux	CCT	CRI	Optics		Weight
SK01WW45 MWH	MWH	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	110 lm	65 lm	3000K	80	45°		0,03 kg
SK01NW45 MWH	MWH	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	135 lm	83 lm	4000K	80	45°		0,03 kg
SK01WW45 MBK	MBK	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	110 lm	65 lm	3000K	80	45°		0,03 kg
SK01NW45 MBK	MBK	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	135 lm	83 lm	4000K	80	45°		0,03 kg
SK01WW45 AL	AL-AN	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	110 lm	65 lm	3000K	80	45°		0,03 kg
SK01NW45 AL	AL-AN	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	135 lm	83 lm	4000K	80	45°		0,03 kg

SK02

FINISHING AVAILABLE

MWH MBK AL-AN



Code	Finishing	LED type	Power	Output current /voltage pdriver	Driver	LED flux	System flux	CCT	CRI	Optics		Weight
SK02WW45 MWH	MWH	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	110 lm	65 lm	3000K	80	45°		0,03 kg
SK02NW45 MWH	MWH	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	135 lm	83 lm	4000K	80	45°		0,03 kg
SK02WW45 MBK	MBK	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	110 lm	65 lm	3000K	80	45°		0,03 kg
SK02NW45 MBK	MBK	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	135 lm	83 lm	4000K	80	45°		0,03 kg
SK02WW45 AL	AL-AN	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	110 lm	65 lm	3000K	80	45°		0,03 kg
SK02NW45 AL	AL-AN	POWER LED CREE	1x1W	350 mA / 2-4V DC	Excluded	135 lm	83 lm	4000K	80	45°		0,03 kg

